

## PTFE Fortified, Tackifier, Rust Inhibited, UV Tracer

A lithium soap thickened, light viscosity, synthetic hydrocarbon grease. For the lubrication of cams, sliding surfaces, small gear trains, and mechanical linkages of switch gears. Contains modifier for improved adherence.

GM: 9986113

Lubricant Properties		Typical Value	Test Method
<b>Recommended Service Range (°C)</b>		-40 to 125	
<b>Thickener</b>		Lithium Soap	
<b>Base Oil</b>	Type	Polyalphaolefin	
	Kinematic Viscosity	40°C	32.6 cSt
		100°C	5.7 cSt
	Viscosity Index		135
	Flash Point	°C	268
	Pour Point	°C	-62
Typical Properties of the Grease		Typical Value	Test Method
<b>Color, Appearance</b>		off-white	
<b>Penetration (1/10 mm)</b>	NLGI Grade	2	ASTM D-217
	Unworked		292
	Worked	60X	280
<b>Oil Separation</b>	24 hour(s)	100°C	2.2
<b>Evaporation</b>	24 hour(s)	100°C	0.1
			ASTM D-6184
			NYE CTM

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product SDS for detailed safety information on this product. (1504)