

PTFE Fortified, Tackifier, Rust Inhibited, UV Tracer

A lithium soap thickened, light iscosity, synthetic hydrocarbon grease for lubrication of cams, sliding surfaces, small gear trains, and mechanical linkages of switch gear. Excellent for wide temperature performance.

Lubricant Properties		Typical Value	Test Method
Recommended Service Range (°C)		-40 to 125	
Thickener		Lithium Soap	
Base Oil	Type	Polyalphaolefin	
	Kinematic Viscosity	-40°C	8400 cSt
		40°C	32.6 cSt
		100°C	5.7 cSt
	Viscosity Index		135
	Flash Point	°C	245
	Pour Point	°C	-60
Typical Properties of the Grease		Typical Value	Test Method
Color, Appearance		Off-White, Smooth	
Penetration (1/10 mm)	NLGI Grade	3	ASTM D-217
	Unworked	244	ASTM D-217
	Worked	60X	252
		25°C	ASTM D-217
Density		0.89 g/cm ³	ASTM D-70
Oil Separation	24 hour(s)	100°C	1
Evaporation	24 hour(s)	100°C	0.1

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product SDS for detailed safety information on this product. (1508)